

DIALOG 20 is the compact, feature-rich and complete 2 Channel Wireless Microphone System that consists of Receiver with built-in antenna, all types of Transmitters – Boundary tabletop, Gooseneck podium, Handheld, Beltpack and Docking Station.

Worldwide RF Spectrum

- + 2.4 GHz universal band
- + No license restrictions
- + No country, locale restrictions

Compact Receiver

- + Small form-factor
- + Rack-shelf, wall, ceiling mountable
- + Detachable antenna

Modular Components

- + Field-replaceable components
- + Standard AA-size batteries

Robust & Secured System

- + Adaptive frequency-hopping spread spectrum
- + Interference-free
- + 128 bit AES encryption

ClearOne Native Connection

- + Single cable for power, audio, control
- + Daisy-chains with CONVERGE® Pro 2 &
- + Beamforming Mic Array 2

Power Options

- + Receiver power: Micro-USB, PoE, P-link
- + Transmitter power: Batteries, Micro-USB





VENUES

Classrooms

Training Rooms

Huddle Rooms

Media Carts



2 Channel Wireless Microphone System









PRODUCT SPECIFICATIONS

DIALOG 20 - 2 Channel Wireless Microphone System:

• Frequency Response: 20Hz to 20kHz

• Audio Sampling: 24bit 48kHz

• RF Frequency: 2.4 GHz to 2.483 GHz

• Adaptive Frequency Hopping Spread Spectrum

• Signal to Noise ratio: 109 dB(A)

Encryption: AES 128bitRF Range: 30mLatency: <4ms

Receiver (Base Station)

• RF Sensitivity: -89 dBm

• RF Output Power: 1 mW

• Display: OLED (for each receiver channel, on the front panel)

• Audio Output: +4dBu

• Audio connection: XLR, 1/4"TRS

• Antenna Connection: TNC 50 ohm

• GPIO: 3.5mm 6 pin terminal block

• Power Supply: Micro-USB / PoE / P-link

• P-Link: Peripheral link for CONVERGE Pro 2 & Beamforming Mic Array 2

• Power Consumption: 2W

• Antenna: Built-in dipole Antenna. Antenna can be extended to 10 or 20 ft

• Mounting: Rack-shelf, wall, ceiling mountable

• Dimension [W x H x D]: 172 x 42.3 x 127.5mm (6.77" x 1.67" x 5.01")

• Weight: 0.43kg (0.95lbs)

Transmitters (Microphones)

• RF Output Power: 1mW, 10mW

• Display: OLED (Handheld and Beltpack only)

• Power Supply: NiMH, Alkaline, USB, Charger Dock

• Battery: Standard AA size, rechargeable batteries

• 2 AA batteries for Tabletop, Handheld and Beltpack

• 4 AA batteries for Gooseneck

• Talktime: 2 AA= ~12hrs, 4 AA= ~15hrs

• Programmable button: PTT (Push to talk), PTM (Push to mute), Toggle

Part Numbers

DIALOG 20 Receiver:

DIALOG 20 Transmitters:

Wireless Tabletop / Boundary Cardioid	910-6101-001
Wireless Tabletop / Boundary Omni	910-6101-011
• Wireless Gooseneck / Podium Cardioid, 6" neck	910-6102-061
• Wireless Gooseneck / Podium Cardioid, 12" neck	910-6102-121
• Wireless Gooseneck / Podium Cardioid, 18" neck	910-6102-181
Wireless Handheld with SACOM H18,	
Condenser, Cardioid Microphone capsule	910-6103-001
• Wireless Handheld Transmitter with Audix OM3,	
Dynamic, Super Cardioid Microphone capsule	910-6103-011
• Wireless Handheld Transmitter with Audix OM5,	
Dynamic, Hyper Cardioid Microphone capsule	910-6103-021
Wireless Beltpack Transmitter	910-6104-001

Accessories:

Lavalier Omni Microphone for Beltpack	910-6004-010
Lavalier Cardioid Microphone for Beltpack	910-6004-040
Single-ear Headset Omni, Black	
Microphone for Beltpack	910-6004-020
Single-ear Headset Omni, Tan	
Microphone for Beltpack	910-6004-020-T
Docking Station (8 bay charging station)	910-6000-800
• Wireless Extension cables pair for Dipole Antenna,	
10 Ft, with mounting adapter	910-6105-011
• Wireless Extension cables pair for Dipole Antenna,	

25 Ft, with mounting adapter......910-6105-021

SALES AND INQUIRIES

North America

Tel: +1 801.975.7200 TollFree: +1 800.945.7730

TechSales: +1 800.705.2103 Fax: +1 801.303.5711

sales@clearone.com

Europe

Tel: +1.800.945.7730 global@clearone.com Middle East

Tel: +1.800.945.7730 global@clearone.com Asia Pacific

Tel: +1.800.945.7730 global@clearone.com Other Regions

Tel: +1.800.945.7730 global@clearone.com